

PAPERMATCH® T 4776/10

Product Description

PAPERMATCH® T 4776/10 is a specialty masterbatch formulated to impart paper-like appearance to LLDPE. PAPERMATCH® T 4776/10 is a white, medium opacity grade designed to provide increased stiffness and a smooth surface texture.

General

Material Status	• Commercial: Active
Availability	• North America
Uses	• Masterbatch
Processing Method	• Blown Film

Physical	Nominal Value (English)	Nominal Value (SI)	Test Method
Additive Content (Ash)	62.0 %	62.0 %	ASTM D5630
Specific Gravity	1.59	1.59 g/cm ³	ASTM D792
Moisture Content	< 800 ppm	< 800 ppm	Internal Method

Usage

PAPERMATCH® T 4776/10 is typically recommended for use at 50% addition levels in LLDPE blown film applications.

Regulatory

PAPERMATCH® T 4776/10 is made only from FDA recognized materials. Usage restrictions may apply. Detailed information is available upon request.

Packaging & Storage

PAPERMATCH® T 4776/10 is typically packaged in foil-lined cartons or moisture barrier bags. PAPERMATCH® T 4776/10 can be stored for up to a maximum of 12 months at 25°C for optimum performance. Higher temperatures might reduce storage time considerably.